

QUALITY. TECHNOLOGY. INNOVATION.





Outline

- Introduction about BEL
- Requirements
- Approach
 - Tools used :MATLAB Sensor Fusion Tracking Toolbox (SFTT) , CODER
 - Method employed : Development Phase I IV
- Results
 - Comparison with different approaches
 - Comparison with Original Equipment Manufacture (OEM)system
- Key takeaways
- Looking forward for...



ABOUT BEL

- ❖ BEL is PSUs under the Ministry of Defence, India.
- BEL design, develop and manufactures a wide range of products in the following fields
 - Radars
 - Electronic Warfare System
 - Defence Communication
 - Tank Electronics
 - Opto Electronics and Semiconductors
 - Missile System and Tank Electronics
 - EVM and VVPAT and many more...
- Major customers of BEL comprise of Indian Army, Navy, Air Force, Paramilitary, Coast Guard and many more.












RADAR PROJECT SCHEMATIC



STC: Sensitivity Time Control

FTC: Fast Time Control

CFAR :Constant False Alarm Rate



REQUIREMENTS

- □ Development of **field deployable multi-target tracking module** using **Sensor Fusion**Tracking Toolbox and MATLAB coder.
- Evaluation of performance in **Coastal Surveillance** scenario.

CHALLENGES

- Small target tracking amidst sea clutter
- Reduced false track initiation in high clutter conditions
- Faster track initiation & better maintenance
- Attribute extraction for target classification
- ☐ Deployable code generation without dependencies on external libraries



APPROACH



EVALUATING
SFIT IN MATLAB
WITH RECORDED
DATA

COMPARISION
OF RESULT WITH
RECORDED
TRACK REPORTS

Phase-II

USING MULTIPLE TRACK LINES

USING COVARIANCE FUSION

Phase-III

C/C++ CODE GENERATION


WRAPPER FUNCTION FOR INTERFACE WITH SP CHAIN

Phase-IV

CUSTOM ENHANCEMENTS IN C++ CODE

KNOWLEDGE BASED TRACKING







DEVELOPMENT PHASE - I


- Evaluating performance of trackerGNN and trackerTOMHT modules in Matlab-SFTT with field recorded data(detections).
 - Tuning tracker initiation, filter and maintenance parameters
 - Evaluating performance w.r.t track kinematics accuracy and maintenance, by changing assignment methods, cost matrix computation, etc.

```
tracker =
trackerGNN('FilterInitializationFcn',..
@initcaekf,...
'MaxNumTracks',1000,...
'Assignment','Jonker-Volgenant',...
'AssignmentThreshold',50,...
'TrackLogic','History',...
'DeletionThreshold',[6 8], ...
'ConfirmationThreshold',[8 10],...
'HasCostMatrixInput',true);
```

```
tracker =
trackerTOMHT('FilterInitializationFcn',...
@custcaekf, ...
'ConfirmationThreshold', 25,...
'MaxNumSensors', 1, ...
'DeletionThreshold', -5, ...
'AssignmentThreshold', [0.5,0.7,1]*50,...
'MaxNumHypotheses', 2,...
'MaxNumTracks',1000,...
'MaxNumTracks',1000,...
'NScanPruning','Hypothesis',...
'HasCostMatrixInput',true,...
'FalseAlarmRate',1e-5);
```




RECORDED DATA-295 SCANS



RADAR – POSITION
NAVIGATIONAL-TL PLOTS
SLOW-TL-PLOTS
FAST-TL-PLOTS
HELICOPTER-TL-PLOTS
TERMA- TRACKS




RESULTS USING MATLAB SFTT-GNN MULTIOBJECT TRACKER






RESULTS USING MATLAB SFTT-TOMHT MULTIOBJECT TRACKER





DEVELOPMENT PHASE - II

Use of Multiple-Track Lines for load reduction




Use of covariance fusion for correlating tracks from all track lines

```
X(:,t) = confTracks{h} (fusionIDS{cTrk} (t)).State;
P(:,:,t) = confTracks{h} (fusionIDS{cTrk} (t)).StateCovariance;
[Xcorr,Pcorr] = fusexcov(X,P); %Cross-covariance fusion
```




RESULTS (CONTD.)





TRACK MAINTENANCE FOR TWO DATASETS





DEVELOPMENT PHASE - III

Deployable C++ code generation using MATLAB Coder

```
load detectiondata.mat
compInputs = {detections simTime};
tracker kernel(compInputs{1}, simTime);
codegen tracker kernel -args compInputs;
function [confirmedTracks, numTracks, ~] =
tracker kernel.m(detections, time)
    persistent tracker
    if isempty(tracker)
         tracker = trackerTOMHT('FilterInitializationFcn',
    @initcaEKF,...
          'MaxNumHypotheses', 5,...
          'MaxNumTracks',1000,...
          'MaxNumSensors',1,...
          'NScanPruning', 'Hypothesis');
    end
    [confirmedTracks, ~, ~, information] = tracker(detections, time);
    numTracks = tracker.NumTracks;
end
```

Wrapper function is developed for interfacing the C++ Code with the signal processer chain.




DEVELOPMENT PHASE - IV

- Custom Enhancements in C++ code for introducing Knowledge based tracking methods such as:
 - Utilization of **zones** and **map** information
 - Using plot attributes such range spread ,azimuth spread and plot amplitude for association
 - Adaptation in Confirmation, Association and Deletion Thresholds w.r.t variable clutter density
 - Optimizing memory allocations and introducing parallel processing architecture for multiple track lines with correlation.




PLOT ATTRIBUTES





STATUSF





BENEFITS OF USING MATLAB

- Object Oriented Approach
- ❖ The ability to auto-generate C code, using MATLAB Coder
- Wide variety of readily available packages and Toolbox
- Complex Tracker Algorithms are available out of the box.
- Easy to prove and evaluate the concepts
- Saves money and time
- User friendly



KEY TAKE AWAYS

- Using MATLAB SFTT for evaluating Multi-Target Tracker and
 - **Estimation Filters**
- ☐ Using cross-covariance fusion for track-to-track correlation
- ☐ Using MATLAB CODER for deployable C++ code generation
- ☐ Employing Knowledge based tracking methods for improving track maintenance



LOOKING FORWARD FOR

- Multi-sensor data fusion (viz. Radar, AIS etc)
- Attribute based Tracking and data fusion
- Target classification
- ☐ Deployable code generation for these modules





" Looking forward to a long and fruitful association "
THANK YOU